

# ELC BATTERY CHARGERS



Constant Voltage / Current · Temperature Compensated · Alarm Options

## Industry Leading

---

## Cost Effective

---

## Field Proven

---

## Wide Variety of DC Output Options

---

## Made in the USA



National Railway Supply | 1.800.357.3572 | nrsga.com

- Dual AC input voltages - 115/230 Vac, 50/60/100 Hz
- Proven SCR technology - constant voltage and constant current charge control with excellent AC line regulation and precise control
- Selectable DC float voltage - battery float voltage can be precisely set and is highly accurate
- Flexible battery types - Valve Regulated Lead-Acid (VRLA), Flooded/Vented Lead-Acid, Nickel-Cadmium (NiCd)
- Battery temperature compensation with controlled limits
- Filtered DC output
- Optional integrated current or current/voltage monitor/alarm with Form C, dry contact relay(s)
- DC output ammeter
- LED status indicators
- Transient protection - AC input and DC output surge suppression
- Natural convection cooled
- Wide operating temperature range of -40 °C to +71 °C
- Meets or exceeds all AREMA specifications

# SPECIFICATIONS

MODEL	AC INPUT			DC OUTPUT		NO. OF CELLS Lead Acid Nickel Cadmium	PHYSICAL SIZE		CURRENT MONITOR/ ALARM (M) OPTION *	CURRENT & VOLTAGE MONITOR/ ALARM (CVM) OPTION *	
	Voltage (Volts)	Frequency (Hertz)	Current (Amps at full power)	Voltage Range	Current Limited		Size (Inches)				Weight (lbs.)
ELC 12/10	115(108-128) 230(216-256)	50/60/100 50/60/100	3.5 1.7	10-17	10A	5-7 LA 7-11 NiCad	12.00 W 5.20 D 12.00 H		22	✓	--
ELC 12/20	115(108-128) 230(216-256)	50/60/100 50/60/100	6 3	10-17	20A	5-7 LA 7-11 Ni Cad	<i>Standard</i> 14.25 W 8.70 D 8.70 H	<i>CVM Option</i> 20.00 W 8.70 D 9.86 H	30	✓	✓
ELC 12/40	115(108-128) 230(216-256)	50/60/100 50/60/100	14 7	10-17	40A	5-7 LA 7-11 NiCad	20.00 W 8.70 D 9.86 H		57	✓	✓
ELC 12/60	115(108-128) 230(216-256)	50/60/100 50/60/100	17 9	10-17	60A	5-7 LA 7-11 NiCad	19.50 W 12.50 D 12.75 H		73	--	✓
ELC 24/10	115(108-128) 230(216-256)	50/60/100 50/60/100	7 3.5	20-35	10A	8-14 LA 13-23 NiCad	14.25 W 8.70 D 8.70 H		30	✓	--
ELC 24/30	115(108-128) 230(216-256)	50/60 50/60	16 7.5	20-35	30A	8-14 LA 13-23 NiCad	20.00 W 8.70 D 9.86 H		58	✓	✓
ELC 120/6	115(108-128) 230(216-256)	50/60/100 50/60/100	13.5 7	100-150	6A	40-60 LA 60-92 NiCad	20.00 W 8.70 D 9.86 H		75	--	--
ELC 120/12	115(108-128) 230(216-256)	50/60 50/60	26 13	100-150	12A	40-60 LA 60-92 NiCad	19.50 W 12.50 D 12.75 H		100	--	--

\* Contact us for monitor/alarm option availability with other models.



**NATIONAL RAILWAY SUPPLY**

P. O. BOX 13727

SAVANNAH, GA 31416

1-800-357-3572

Website: [www.nrsga.com](http://www.nrsga.com)

Email: [Info@nrsga.com](mailto:Info@nrsga.com)